

Product certificate **K44354/04**



Issued

2021-08-15

Replaces

K44354/03

Page

1 of 2

Flexible connecting hoses

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Bremboflex S.r.I.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K622 "Flexibele aansluitleidingen" dated 01-02-2012

which covers the requirements of

EN13618:2011: "Flexible hose assemblies in drinking water installations - Functional requirements and test methods".

Ron Scheepers

Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchilllaan 273

Postbus 70

2280 AB RIJSWIJK

The Netherlands

Tel. +31 88 998 44 00 Fax +31 88 998 44 20

NII I/i.... info@I/i...

NL.Kiwa.info@Kiwa.com

www.kiwa.nl

Company

Bremboflex S.r.l.

Via Tresolzio 105

24030 BREMBATE SOPRA

Italy

Tel. 035 620238

info@bremboflex.it

www.bremboflex.it





Certification process consists of initial and regular assessment of:

- quality system
- product

page 2 of 2

Flexible connecting hoses

PRODUCT SPECIFICATION

The products mentioned below belong to this technical approval-with-product certificate

Design:

- G 3/8" brass female connection nut Connecting ends*:

- G 3/8" brass female connection nut - G 1/2" brass female connection nut - Elbow G 3/8" brass female connection nut - M8 x 1 male threaded joint - G 1/2" brass female connection nut - Straight fitting for compression joint - M10 x 1 male threaded joint

- Straight fitting for compression joint

PEX Inner hose:

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this

MARKING

The Kiwa®-mark products are marked with the word mark "KIWA **, or the abbreviated mark KKI.

Place of the mark:

· on the flexible hoses (clamp bush).

Compulsory specifications:

- name or mark of manufacturer: on the flexible hose (clamp bush);
- if supplied with a compression fitting, then, in addition, the manufacturer's mark and nominal size: on the coupling nut.
- data or code indicating the date of production: on the flexible hose (clamp bush);
- maximum allowed water temperature: on the flexible hose (clamp bush).

Method of marking:

- · non-erasable;
- · visible after assembly

APPLICATION AND USE

The flexible connecting hoses are intended for application in drinking water installations with a static water pressure of maximum 1000 kPa and a maximum water temperature of 70 °C.

Flexible connecting hoses may be used as an integrated part of the appliance.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- · the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

· Bremboflex S.r.l.

and, if necessary,

• Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.

^{*} The hoses can be fitted with any of the mentioned connecting ends in any possible combination.